

VOLTAGE AND RESISTANCE PRODUCTS

## Microohmmeter and Bond Tester

## 技术咨询和询价:010-68940148



Model R1L-B



 Rugged: MIL PRF2880F Class 3 (R1L-BR)

• Low Cost: (R1L-B)

• Portable: Long Rechargeable

**Battery Life** 

• Ranges:  $2 \text{ m}\Omega$  to  $20 \Omega$ 

Accuracy: 0.25% of reading

• Resolution: 1μΩ

• Simple Operation

• Offset Compensation

The R1L-B series Ohmmeter/Bonding Tester is a digital microohmmeter designed to measure resistances up to  $20~\Omega$ . It may be used in applications such as ground bond tests, motor, transformers, switch, circuit breaker, circuit resistance and other contact and connection resistance tests. The instruments utilize the four-terminal Kelvin technique to eliminate errors caused by the resistance of the connecting cables. Resistance readings are viewed on a  $3\frac{1}{2}$  digit display, reading from 1.999 to 199.9.

Front panel controls are simply a POWER ON-OFF switch and a rotary 5 range selector switch. Measurement connections are made via four front panel low thermal banana jacks.

Both instruments are battery operated and recharged from line power. The BR model is more suitable for portable "rugged" applications while the B model is suitable mainly for "in plant" environments.



VOLTAGE AND RESISTANCE PRODUCTS

## **Specifications**

Resistance	Ranges	and '	Test (	Currents
Kesisidilee	Kanaes	uliu	1631 1	- OII <del>-</del> III -

Full Scale	Resolution	Accuracy	Test Current
1.999 mΩ	1 μΩ	0.25% of reading ± 1 count	1.4 A
19.99 mΩ	10 μΩ	0.25% of reading ± 1 count	140 mA
199.9 mΩ	100 μΩ	0.25% of reading ± 1 count	14 mA
1.999 Ω	$1~\text{m}\Omega$	0.25% of reading ± 1 count	1.4 mA
19.99 Ω	$10\text{m}\Omega$	$0.25\%$ of reading $\pm$ 1 count	140 μΑ
Calibration	Operates as s	specified for at least one year wit	hout the need for recalibration.

Internal controls are available to recalibrate all ranges.

**Environmental Operating Temperature:** 0 to +50 ° C Storage Temperature: -40 to +71° C

**Physical and Power** R1L-B R1L-BR

**Size:** 11.6"W X 4H" X 6.8"D

Weight: 3.6 lb

Size: 10"W X 5"H X 9"D

Weight: 6.7 lb

Power: 120/240VAC 50/60 Hz

3 High Capacity 'C' NiCad rechargeable batteries included

## **Accessories**

HTP-100	Pistol Grip Probes
KTL-100	Kelvin Clip Leads
KAK-1M	Kelvin Alligator Clips
HKC-100	Large Kelvin Test Lead Set
BKP-10	Standard Kelvin Probe
MKP-6	Kelvin Probe
MCP-6	Miniature Kelvin Coaxial Probe





**BKP-10 Pin Options** 




BKP-10 HTP-100 Pistol Grip **KTL-100** 





MKP-6 Probe Set with "B" Style Pins Installed



**MKP-10 Pin Options**