

VLF SINE 34 kV

Test system for medium voltage cables



- High test capacity of 5 μ F
- Suitable for outdoor use (IP 54)
- Single-button operation
- Integrated safety system
- Reporting
- Continuous duty cycle

VLF SINE 34kV DESCRIPTION

The **VLF sine wave 34 kV** is a compact, robust and portable VLF sine wave test system for medium voltage cables.

The design, optimized for rapid transportation and quick setup, and the continuous duty cycle make the system an ideal tool for routine cable testing.

For both 0.1 Hz sine wave voltage tests and rectangular or DC voltage tests, the **VLF sine wave 34 kV** fulfils the highest demands of test voltage quality and stability. Moreover, the integrated "breakdown detection" shuts down the test voltage in the event of an excessive charge current and guarantees limited damage to the cable.

Consistent single-button operation combined with a sophisticated operating concept allows fast and targeted use of the system.

The integrated USB port enables seamless reporting.

The **VLF sine wave 34 kV** is a multi-purpose device: it can be used for cable testing, sheath testing, and in combination with the optional step voltage probe ESG NT2, for sheath fault pinpointing.

The system can also be used as a voltage source for the optional tan delta measurement and partial discharge attachments and can be easily expanded to a universal testing and diagnostic system.

VLF SINE 34 kV Test system for medium voltage cables

TECHNICAL DATA*

Output voltage

VLF sine wave	0 ... 24 kV _{RMS} / 0 ... 34 kV _{peak}
DC voltage	± 0 ... 34 kV
VFL rectangular voltage	0 ... 34 kV
Precision	± 1 %
Resolution	0.1 kV

Output current

Measuring range	0 ... 14 mA
Precision	± 1 %
Resolution	1 µA

General

Frequency range	0.01 Hz ... 0.1 Hz autom. frequency adjustment
Output	0.6 µF @ 0,1 Hz at 24 kV _{RMS} 5 µF @ 0,01 Hz at 21 kV _{RMS}
Input voltage	100 V ... 260 V, 50/60 Hz, 400 VA
Sheath testing	0 ... 5 kV, 0 ... 10 kV DC
Sheath fault pinpointing	0 ... 5 kV, 0 ... 10 kV DC, Pulse rate 1:3 and 1:4
Safety	Earth loop ground monitoring, autom. discharging of the test object
Dimensions (W x H x D)	520 x 450 x 300 mm
Weight	25 kg
Protection class	IP 20/IP 54 (operation/transportation)
Operating temperature	- 20 °C ... + 55 °C
Storage temperature	- 25 °C ... + 70 °C

VLF SINE 34kV FEATURES

- Testing without operational interruptions
- AC testing in compliance with DIN VDE, EN, IEEE
- Compact, rugged, lightweight and IP 54 for transportation
- Sheath testing and sheath fault pin-pointing acc. to IEC 60229
- Maximises user safety through automatic discharge of the test object and earth loop ground monitoring
- Breakdown detection and load recognition (R, C)
- Quick & easy logging, and updates via USB port

SCOPE OF DELIVERY

- VLF sine wave 34 kV
- Accessory bag
- HV connection cable 5 m
- Mains cable / grounding cable
- USB stick for reporting
- Easyprot reporting software

ORDERING INFORMATION

Product	Order no.
VLF sine wave 34 kV consisting of:	
VLF sine wave 34 kV test system	890026134
Mandatory selection lead set (1x)	
Lead set „standard“	890020757
Lead set „NAFTA“	2008779
Mandatory selection mains cable (1x)	
Mains cable EU	810000024
Mains cable UK	118307335
Mains cable US	502025220
Mains cable AUS	90020435
Options:	
External safety unit for stand-alone systems	128309600
HV connection cable VLF sine wave 34, 10m	2009692
HV connection cable VLF sine wave 34, 15m	118303277
HV connection cable VLF sine wave 34, 10m (NAFTA)	2008781
HV connection cable VLF sine wave 34, 15m (NAFTA)	2008782
External tan delta attachment (see tan delta attachment datasheet)	
PDS 62-SIN PD attachment (see PDS 62-SIN datasheet)	
Calibration certificate VLF sine wave 34 kV	2004131

The information in this document is subject to change without notice and should not be construed as a commitment by Megger Germany. Megger Germany assumes no responsibility for any errors that may appear in this document.